



ALLOWANCE	
UNDER 3	± 0.1
3 TO 6	± 0.15
6 TO 15	± 0.2
15 TO 50	± 0.25
50 OVER	± 0.3

Specifications:
 Rating : DC 50V, 1A.
 Force: 5-40N.
 Contact resistance:
 Less than $30m\Omega$.
 Insulation resistance:
 Over $100M\Omega$ on DC 500V
 measured.
 Voltage withstand :
 AC 500V, For 1 minute.

9	WASHER-D	SPCC $\delta 0.5$	1	NI PLATED
8	SCREW	BRASS	1	NI PLATED
7	SOCKET	BRASS	1	NI PLATED
6	WASHER-C	SPCC $\delta 0.7$	1	NI PLATED
5	WASHER-B	PF	1	BROWN
4	WASHER-A	PF	2	BROWN
3	TERMINAL-C	BRASS $t=0.7$	1	AG PLATED
2	TERMINAL-B	BRONZE $t=0.7$	1	AG PLATED
1	TERMINAL-A	BRONZE $t=0.7$	1	AG PLATED
NO:	PART NAME	MATERIAL	QTY	FINISHING

MODEL NO : SJ-6348	ALLOWANCE:	DRAWN BY:
TYPE: 6.35 PHONE JACK	UNIT: mm	CHECKED BY:
MATERIAL NO :	SCALE:	APPROVED BY:
PROJECTION	 ZWEE CO., LIMITED	